

Race Condition Vulnerability

Copyright © 2017 Wenliang Du, All rights reserved.

- 7.1. Does the following Set-UID program have a race condition vulnerability?

```
if (!access("/etc/passwd", W_OK)) {
    /* the real user has the write permission*/
    f = open("/tmp/X", O_WRITE);
    write_to_file(f);
}
else {
    /* the real user does not have the write permission */
    fprintf(stderr, "Permission denied\n");
}
```

- 7.2. Assume we develop a new system call, called `faccess(int fd, int mode)`, which is identical to `access()`, except that the file to be checked is specified by the file descriptor `fd`. Does the following program have a race condition problem?

```
int f = open("/tmp/x", O_WRITE);
if (!faccess(f, W_OK)) {
    write_to_file(f)
} else {
    close(f);
}
```

- 7.3. How many race conditions does attackers have to win in the following program?

```
int main()
{
    struct stat stat1, stat2;
    int fd1, fd2;

    if (access("/tmp/XYZ", O_RDWR)) {
        fprintf(stderr, "Permission denied\n");
        return -1;
    }
    else fd1 = open("/tmp/XYZ", O_RDWR);

    if (access("/tmp/XYZ", O_RDWR)) {
        fprintf(stderr, "Permission denied\n");
        return -1;
    }
    else fd2 = open("/tmp/XYZ", O_RDWR);

    // Check whether fd1 and fd2 have the same inode.
    fstat(fd1, &stat1);
    fstat(fd2, &stat2);
}
```

```

    if(stat1.st_ino == stat2.st_ino) {
        write_to_file(fd1);
    }
    else {
        fprintf(stderr, "Race condition detected\n");
        return -1;
    }
    return 0;
}

```

- 7.4. In the `open()` system call, it first checks whether the user has the required permission to access the target file, then it actually opens the file. There seems to be a check-and-then-use pattern. Is there a race condition problem caused by this pattern?
- 7.5. The least-privilege principle can be used to effectively defend against the race condition attacks discussed in this chapter. Can we use the same principle to defeat buffer-overflow attacks? Why or why not? Namely, before executing the vulnerable function, we disable the root privilege; after the vulnerable function returns, we enable the privilege back.
- 7.6. The following root-owned `Set-UID` program needs to write to a file, but it wants to ensure that the file is owned by the user. It uses `stat()` to get the file owner's ID, and compares it with the real user ID of the process. If they do not match, the program will exit. Please describe whether there is a race condition in the program? If so, please explain how you can exploit the race condition. The manual of `stat()` can be found online.

```

#include <stdio.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <unistd.h>

int main()
{
    struct stat statbuf;
    uid_t real_uid;
    FILE* fp;

    fp = fopen("/tmp/XYZ", "a+");
    stat("/tmp/XYZ", &statbuf);

    printf("The file owner's user ID: %d\n", statbuf.st_uid);
    printf("The process's real user ID: %d\n", getuid());

    // Check whether the file belongs to the user
    if (statbuf.st_uid == getuid()) {
        printf("IDs match, continue to write to the file.\n");
        // write to the file ...
        if (fp) fclose(fp);
    } else {
        printf("IDs do not match, exit.\n");
        if (fp) fclose(fp);
        return -1;
    }
}

```

```
    }  
  
    return 0;  
}
```

- 7.7. The following root-owned Set-UID program needs to write to a file, but it wants to ensure that the file is owned by the user. It uses `fstat()` to get the file owner's ID, and compares it with the real user ID of the process. If they do not match, the program will exit. Please describe whether there is a race condition in the program? If so, please explain how you can exploit the race condition. The manual of `fstat()` and `fileno()` can be found online.

```
#include <stdio.h>  
#include <sys/types.h>  
#include <sys/stat.h>  
#include <unistd.h>  
  
int main()  
{  
    struct stat statbuf;  
    uid_t real_uid;  
    FILE* fp;  
  
    fp = fopen("/tmp/XYZ", "a");  
    fstat(fileno(fp), &statbuf);  
  
    printf("The file owner's user ID: %d\n", statbuf.st_uid);  
    printf("The process's real user ID: %d\n", getuid());  
  
    // Check whether the file belongs to the user  
    if (statbuf.st_uid == getuid()) {  
        printf("IDs match, continue to write to the file.\n");  
        // write to the file ...  
        if (fp) fclose(fp);  
    } else {  
        printf("IDs do not match, exit.\n");  
        if (fp) fclose(fp);  
        return -1;  
    }  
  
    return 0;  
}
```

- 7.8. If we can lock a file, we can solve the race condition problem by locking a file during the check-and-use window, because no other process can use the file during the time window. Why don't we use this approach to solve the race condition problems discussed in this chapter?
- 7.9. Does the following privileged Set-UID program have a race condition problem? If so, where is the attack window? Please also describe how you would exploit this race condition window.

```
1  filename = "/tmp/XYZ";
2  fd = open (filename, O_RDWR);
3  status = access (filename, W_OK);
   ...
   ... (code omitted) ...
   ...
10 if (status == ACCESS_ALLOWED) {
11     write_to_file(fd);
12 } else {
13     fprintf(stderr, "Permission denied\n");
14 }
```

7.10. Please use the least-privilege principle to fix the race condition problem in the following program.

```
if (access("/tmp/XYZ", W_OK) == ACCESS_ALLOWED) {
    f = open("/tmp/XYZ", O_WRITE);
    write_to_file(f);
}
else {
    fprintf(stderr, "Permission denied\n");
}
```